

## HIGHTEC TURBO HD SAE 15W-40

High-performance engine oil of SAE grade 15W-40 based on selected mineral oils.

### Description

HIGHTEC TURBO HD SAE 15W-40 is a multigrade engine oil of viscosity grade SAE 15W-40 based on selected mineral oils. This product is particularly suitable for vehicles equipped with Otto and diesel engines, with or without turbocharging.

### Application

HIGHTEC TURBO HD SAE 15W-40 is particularly suitable for vehicles equipped with Otto and diesel engines, with or without turbocharging. It is used in vehicles without an extended maintenance interval. The modern design of HIGHTEC TURBO HD SAE 15W-40 makes a wide range of applications possible and ensures safe operation under all operating conditions.

### Approvals

- VW 501 01/505 00

### Equivalent quality in accordance with EU-law as per

- ACEA A3/B4
- API SN
- Fiat 9.55535-G2/D2
- MB 229.1

### This product is also recommended when the following filling instructions are required

- API CF

### Advantages

- Eminently suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner
- Year-round operation with good viscosity-temperature behaviour and high shear stability
- Stable lubricating film, even with hot oil and under excessive loads
- Very low oil consumption
- High level of oxidation protection by means of selected base oils and special additives
- Reliable protection against 'black sludge'
- Proper functioning of hydraulic tappets (hydraulic valve clearance compensation)
- Miscible and compatible with conventional and synthetic engine oils. However, in order to exploit the full benefits of the product HIGHTEC TURBO HD SAE 15W-40, a complete oil change is recommended.



## Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.874
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	14,6
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	104,6
Viscosity index	ASTM D2270	-	144
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	234
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-25
CCS	ASTM D-5293	cP @ °C	5200 @ -20
Total base number	DIN 51639-1	mgKOH/g	min. 10,0
HTHS	ASTM D4683	mPas	4,1

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply ([www.rowe-oil.com](http://www.rowe-oil.com)).

