PRODUCT INFORMATION



HIGHTEC COOL MMU 2

All-purpose, water-miscible cooling lubricant for machining

Description

HIGHTEC COOL MMU 2 is a water-miscible cooling lubricant (free of boron) containing mineral oils with selected EP/AW corrosion protection agents

Application

HIGHTEC COOL MMU 2 forms a milky, stable emulsion when mixed with water.

HIGHTEC COOL MMU 2 is recommended for the machining of cast iron, aluminium and non-ferrous metals.

Advantages

- · Good emulsion stability
- High performance
- Long service life
- Suitable for all applications
- Good starting ability, even with cold mixing water
- It does not contain any secondary alkanol amines and thus complies with TRGS 611
- Chlorine-free

Recommendation

- Machining (drilling, turning, milling) - Grinding Recommended concentration to be used: Machining 5-10% Grinding process: 5-7% Mixing temperature range: 15-20°C

Notes

- Degreasing
- HIGHTEC COOL MMU 2 can be degreased using conventional degreasing media, for example by spray cleaning or immersion cleaning with aqueous-alkaline cleaning agents.
- Storage
- When stored in dry, frost-free rooms and in original, unopened containers the storage period is: 9 months
- Temperature range: 10-35°C

ROWE MINERALÖLWERK GMBH Langgewann 101, D-67547 Worms

Are you looking for the correct oil for your vehicle? Scan this code for the ROWE-oilfinder.

PRODUCT INFORMATION



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0.951
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	35
Density at 20 °C	ASTM D1122	g/ml	0.951
Refractometer factor	-	-	1
Color of the emulsion		visual	milchig-opak
Mineral oil content		wt-%	40 - 48
pH of a 5% emulsion	DIN 51369	-	8,9
Corrosion protection (chip test) grade 0	DIN 51360/2	%	5

These characteristics are typical for current production. The data does not constitute an assurance of properties or a guarantee of suitability for a specific application. Existing legal provisions and regulations that affect handling and usage of the products must be observed by the recipient of our products. ROWE products are continuously being developed. For this reason, ROWE retains the right to change all technical data in this product information at any time without prior announcement. Our current General Delivery and Payment Conditions apply (www.rowe-oil.com).

ROWE MINERALÖLWERK GMBH Langgewann 101, D-67547 Worms



Are you looking for the correct oil for your vehicle? Scan this code for the ROWE-oilfinder.